

ENSTO

PRODUCT SPECIFICATION

2/28/2019



641867722530

KDN302

Mounting box

Code	KDN302
GTIN	641867722530
ENumber	
Name	Mounting box
	Markings 1, PE, 2
Description	The KDN302 mounting box is equipped with a 3-pole EnstoNet coupler NAC32.R/L1 and a 3-pole wire connector KD160.03. The marking of the coupler is 1, PE, 2. The lid is fastened by snapping into place.
Vendor	Ensto Finland Oy
	CE



Technical specification

Dimensions

Weight: 75.7 g

Materials

Material: Polypropylene

Ratings

Rated voltage: 250 V
 Degree of protection: IP21
 Rated current: 20 A
 ETIM 7: EC002600 Box/housing for surface mounting on the wall/ceiling

ETIM

ETIM

Cover model: Suitable for snap-in connector (brand specific)
 Mounting method: Wall-/ceiling mounting
 Material: Plastic

Shape:	Rectangular
Number of inlets:	5
Equipped with:	Clamp
Sealable:	false
Inlet from the rear:	true
Circuit integrity:	None
Rated insulation voltage Ui:	250 V
Length:	121 mm
Weatherproof:	false
For Ex-Zone dust:	None
Type of housing feed-through:	Preembossing
Tackable:	false
For Ex-zone gas:	None
Depth:	21 mm
Cover attachment:	Snapped on
Width:	95 mm
Max. conductor cross section:	4 mm ²
Explosion-tested version:	false
With screening:	false
Degree of protection (IP):	IP21
Castable:	false
Colour:	White
Casting compound included:	false
Surface protection:	Untreated

Packaging

Default package

Unit:	PCS
Size:	100

Pallet package

Unit:	PCS
Size:	2400