

ENSTO

PRODUCT SPECIFICATION

2/28/2019



6418677722547

KDN506

Mounting box

Code	KDN506
GTIN	6418677722547
ENumber	
Name	Mounting box
	Markings 1, 2, PE, N, 3
Description	The mounting box KDN506 is equipped with a 5-pole coupler NAC52.R/L3 and a 4-pole wire connector KD160.04. The marking of the coupler is 1, 2, PE, N, 3. The lid is fastened by snapping into place.
Vendor	Ensto Finland Oy
	CE



Technical specification

Dimensions

Weight: 83.5 g

Materials

Material: Polypropylene

Ratings

Rated voltage: 250 ... 400 V

Degree of protection: IP21

Rated current: 20 A

ETIM 7: EC002600 Box/housing for surface mounting on the wall/ceiling

ETIM

ETIM

Cover model: Suitable for snap-in connector (brand specific)

Mounting method: Wall-/ceiling mounting

Material: Plastic

Shape: Rectangular

Number of inlets:	5
Equipped with:	Clamp
Sealable:	false
Inlet from the rear:	true
Circuit integrity:	None
Rated insulation voltage Ui:	400 V
Length:	121 mm
Weatherproof:	false
For Ex-Zone dust:	None
Type of housing feed-through:	Preembossing
Tackable:	false
For Ex-zone gas:	None
Depth:	21 mm
Cover attachment:	Snapped on
Width:	95 mm
Max. conductor cross section:	4 mm ²
Explosion-tested version:	false
With screening:	false
Degree of protection (IP):	IP21
Castable:	false
Colour:	White
Casting compound included:	false
Surface protection:	Untreated

Packaging

Default package

Unit:	PCS
Size:	100

Pallet package

Unit:	PCS
Size:	2400