

ENSTO

NAC21SL.W

Coupler

Code	NAC21SL.W
GTIN	6418677114861
ENumber	
Name	Coupler EnstoNet White (1, N), low
Description	For flexible, stranded and solid wires. Wire cross-section 0,75-4,0 mm ² . Strain-relief for cables with outer diameter of 2,5-8,5 mm.
Vendor	Ensto Finland Oy ®CECERL



Technical specification

Dimensions

Weight:	11.8 g
Conductor cross-section:	0,75 - 4 mm ²
Dimensions l x w x h:	51x18x20

Temperatures

Max. operating temperature:	+70 °C
Min. installation temperature:	+5 °C
Min. operating temperature:	-30 °C (without mechanical stress)

Materials

Material:	Polyamide 66
-----------	--------------

Colors

Color:	White
--------	-------

Features

Pole markings:	1,N
----------------	-----

Ratings

Rated voltage:	250 V
Degree of protection:	IP20

Flammability rating:	UL 94 V-2
Rated current:	20 A
ETIM class:	EC002560

ETIM

ETIM

Width:	29 mm
Length:	51 mm
Height:	20 mm
Degree of protection (IP):	IP20
Material housing:	Polyamide
Nominal rated current:	20 A
Model:	Plug
Halogen free:	true
Connection type:	Screw connection
Number of poles:	2
Nominal rated voltage:	250 V
Strain relief:	true
Locking mechanism:	Integrated in plug-in connector
Mechanical coding:	true
Contact material:	CuZn
Connection cross section (solid-core):	0.75 ... 4 mm ²
Number of connections per pole:	1
Pollution degree:	2
Pole codification:	L, N
Colour coding/contact insert:	White
Max. continuous temperature resistance contact part:	70 °C
Max. continuous temperature resistance strain relief:	70 °C
Surface finish contacts:	Silver-plated
Rated surge voltage:	4 kV
Connection cross section (fine-strand):	0.75 ... 4 mm ²
Cable diameter:	4.0 ... 10.5 mm

Packaging

Default package

Unit:	PCS
Size:	200
Length:	385 mm
Width:	260 mm
Height:	130 mm
Weight (brt):	2.65 kg
Volume:	13.013

Pallet package

Size:	12600
--------------	-------