

Distribution blocks

Five-pole distribution blocks, three outlets

Installation screws max. ø 3.5 mm, holes 58 mm apart.

Product code	GTIN	Description	Weight	Package
NAD5.B	6418677114809	Black	57 g	10/50
NAD5.W	6418677113260	White	57 g	10/50
NBD5.S	6418677116155	Blue	57 g	10/50
NCD5.G	6418677117572	Grey	57 g	10/50
NCD5.P	6418677118074	Red	57 g	10/50



Five-pole distribution blocks, three-phase continuous, six single-phase outlets

With the distribution block, three-phase supply is branched into six single-phase outlets. Three-phase supply can also be fed through the distribution block to the next distribution block, for example. The distribution block can be fixed to an installation plate with a mounting pad included in the delivery. The mounting pad can be fixed with four screws (max. ø 4.2 mm). No separate mounting pad is required if the distribution block is installed partially inside a lighting rail with a minimum width of 70 mm.

Product code	GTIN	Description	Weight	Package
NAD56.W	6418677724121	One three-phase inlet and outlet, six single-phase outlet, white	117 g	10
NAD56.B	6418677724138	One three-phase inlet and outlet, six single-phase outlet, black	117 g	10
NCD56.P	6418677724145	One three-phase inlet and outlet, six single-phase outlet, red	117 g	10

