

### Socket outlet box, two three-phase continuous inlets phase rotation, with earth, two double sockets

The NAP505 socket outlet box is equipped with two separate three-phase installation coupler inlets for regular (white couplers) and secure (black couplers) power supply, branched into two double socket outlets. This socket outlet box has continuous supply for the outputs with phase rotation in both three-phase groups. The box has an L1 connection.

| Product code | GTIN          | Description                          | Weight | Package |
|--------------|---------------|--------------------------------------|--------|---------|
| NAP505       | 6418677710124 | White and black three-phase couplers | 420 g  | 10      |



### Socket outlet box, three-phase, continuous with earth, two double sockets

The NAP512 socket outlet box has a three-phase installation coupler input, divided into two double sockets. The double sockets have L1 and L2 connections. The Switch box is equipped with a three-phase continuous supply for the outlet.

| Product code | GTIN          | Description                | Weight | Package |
|--------------|---------------|----------------------------|--------|---------|
| NAP512       | 6418677707643 | Three-phase white couplers | 428 g  | 10      |



## Ensto distribution and control units

These units are designed and manufactured individually to meet the customer's project-specific needs. They are given product-specific sale and production codes during the project. The unit's structure enables any project-specific control solutions selected by the designer. We always assess the feasibility of the solution in advance on the basis of the designer's plan. The unit may include components such as circuit breakers, residual-current devices, contactors, bus-control components (including DALI and KNX), control modules, energy meters and other components defined by the customer. The bus-control components have installation-coupler connectivity. The system may also be pre-programmed, making on-site installation quick and easy. The units, which carry position markings, are mounted in the wiring duct on a cable shelf, lighting rails or wall structures. To make the most of the EnstoNet-compatible control and distribution units, they should be installed in a way that enables power supply directly from a power busbar system.

| Product code | GTIN          | Description                                                                         | Weight | Package |
|--------------|---------------|-------------------------------------------------------------------------------------|--------|---------|
| NGU-KNX-DALI | 6418677684449 | Ensto KNX-DALI control unit: human presence and light sensor, curtain motor control | 2.2 kg | 1       |
| NGU-KNX      | 6418677684456 | Ensto KNX control unit for control of lighting and overhead outlet sockets          | 2.2 kg | 1       |
| NGU-ENET     | 6418677684463 | Ensto eNET control unit: RF controlled human presence sensor, curtain motor control | 2.2 kg | 1       |

