



PRODUCT SPECIFICATION

5/25/2017



6418677116148

NBD3.S**Distribution block**

Code	NBD3.S
GTIN	6418677116148
ENumber	
Name	Distribution block EnstoNet Blue
Description	Distribution block with one in (for a socket) and three out (for plugs). The couplers to be connected to the distribution block are specified in the coupling illustration. If needed, the distribution block can be mounted to a base with two screws, max. $\varnothing$ 3,5 mm, distance between mounting holes 38 mm.
Vendor	Ensto Finland Oy ®CE

**Technical specification****Technical specification**

UL Wire range: 14 AWG

Dimensions

Weight: 35.1 g

Dimensions l x w x h: 47x47x43

Temperatures

Max. operating temperature: +70 °C

Min. installation temperature: +5 °C

Min. operating temperature: -30 °C (without mechanical stress)

Materials

Material: Polyamide 66

Colors

Color: Blue

Drawing markings

L: 250 mm

Ratings

Rated voltage: 250 V
Degree of protection: IP20
Flammability rating: UL 94 V-2
Rated current: 20 A
ETIM class: EC002567

US specific

UL Rated voltage: 250 V
UL Rated current: 16 A

ETIM

ETIM

Degree of protection (IP): IP20
Nominal rated current: 20 A
Number of poles: 3
Nominal rated voltage: 250 V
Locking mechanism: Integrated in plug-in connector
Mechanical coding: true

Packaging

Default package

Unit: PCS
Size: 50
Length: 220 mm
Width: 220 mm
Height: 175 mm
Weight (brt): 1.912 kg
Volume: 8.47

Pallet package

Unit: PCS
Size: 4500
Length: 1200 mm
Width: 800 mm
Height: 1030 mm
Weight (brt): 198 kg
Volume: 988.8

