

**NBD3T.S****T-Connector**

Code	NBD3T.S
GTIN	6418677719714
ENumber	
Name	T-Connector EnstoNet Blue
Description	The item is used in connecting a light fitting or other device to the network supplying it. The counter coupling in the fitting is either NBC31.S or NBS31.S fitted in the device by the panel mounting adapter NK3P.S. The T-connector is fed with a NAC32S.W -coupler (or with an installation-ready cableset, where the NAC32S.W is coupled). The installation continues from the T-connector to the next device with a NBC 31S.S (or with an installation-ready cableset, where the NBC 31S.S is coupled).
Vendor	Ensto Finland Oy 

Technical specification**Dimensions**

Weight:	23.2 g
Dimensions l x w x h:	47x44x37

Temperatures

Max. operating temperature:	+70 °C
Min. installation temperature:	+5 °C
Min. operating temperature:	-30 °C (without mechanical stress)

Materials

Material:	Polyamide 66
------------------	--------------

Colors

Color: Blue

Ratings

Rated voltage: 250 V
Degree of protection: IP20
Flammability rating: UL 94 V-2
Rated current: 20 A
ETIM class: EC002567

ETIM

ETIM

Width: 44 mm
Length: 47 mm
Height: 37 mm
Degree of protection (IP): IP20
Material housing: Polyamide
Nominal rated current: 20 A
Number of outputs: 2
Number of inputs: 1
Halogen free: true
Number of poles: 3
Nominal rated voltage: 250 V
Locking mechanism: Integrated in plug-in connector
Mechanical coding: true
Contact material: CuZn
Pollution degree: 2
Colour coding/contact insert: Blue
Max. continuous temperature resistance contact part: 70 °C
Max. continuous temperature resistance strain relief: 70 °C
Surface finish contacts: Silver-plated
Rated surge voltage: 4 kV
Type of distributor: T-distributor
Type of integrated switching: None
Mounting possibility: With separate adapter

Packaging

Default package

Unit: PCS
Size: 50
Length: 220 mm
Width: 220 mm
Height: 125 mm
Weight (brt): 1 kg

Volume: 6.05

Pallet package

Unit: PCS

Size: 6250

Length: 1200 mm

Width: 800 mm

Height: 1025 mm

Weight (brt): 192 kg

Volume: 984

