



PRODUCT SPECIFICATION

3/5/2019



6418677700712

NCC52.P

Coupler

Code	NCC52.P
GTIN	6418677700712
ENumber	
Name	Coupler EnstoNet 5-pole screw coupler, socket, red (1, 2, PE, N, 3)
Description	
Vendor	Ensto Finland Oy 

Technical specification

Technical specification

UL Wire range: 12 ... 18 AWG

Dimensions

Weight: 16.5 g
 Conductor cross-section: 0,75 - 4 mm²
 Dimensions l x w x h: 31x59x18

Temperatures

Max. operating temperature: +70 °C
 Min. installation temperature: +5 °C
 Min. operating temperature: -30 °C (without mechanical stress)

Materials

Material: Polyamide 66

Colors

Color: Red

Features

Pole markings: 1,2,PE,a+,b-

Ratings

Rated voltage: 250 ... 400 V

Degree of protection:	IP20
Flammability rating:	UL 94 V-2
Rated current:	20 A
ETIM 7:	EC002566 Device connection for plug-in building installation

US specific

UL Rated current:	16 A
-------------------	------

ETIM

ETIM

Connection type:	Screw connection
Colour housing:	Red
Colour of the separate adapter piece:	Without adapter piece
Surface finish contacts:	Silver-plated
Mechanical coding:	true
Length:	31 mm
Number of connections per pole:	1
Max. continuous temperature resistance contact part:	70 °C
Number of poles:	5
Rated current:	20 A
Rated voltage:	400 V
Colour coding/contact insert:	Red
Built-in version:	Built-in part/plug-in connection
Connection size thread:	M3
Locking mechanism:	Integrated in plug-in connector
Halogen free:	true
Model:	Bus
Material housing:	Polyamide (PA)
Angle of plug:	Straight
Max. continuous temperature resistance strain relief:	70 °C
Degree of protection (IP):	IP20
Width:	59 mm
Pollution degree:	2
Height:	18 mm
Rated surge voltage:	4 kV
Connection cross section (solid-core):	0.75 ... 4 mm ²
Connection cross section (fine-strand):	0.75 ... 4 mm ²
Contact material:	CuZn

Packaging

Default package

Unit:	PCS
-------	-----

Size:	100
Length:	220 mm
Width:	220 mm
Height:	125 mm
Weight (net):	1.01 kg
Weight (brt):	1.146 kg
Volume:	6.05

Pallet package

Unit:	PCS
Size:	12500

