

ENSTO

NCC52S.GX2

Coupler

Code	NCC52S.GX2
GTIN	6418677710407
ENumber	
Name	Coupler EnstoNet Grey (1, N, PE, a+, b-), 5/pack
Description	
Vendor	Ensto Finland Oy
	

Technical specification

Technical specification

UL Wire range: 12 ... 18 AWG

Dimensions

Weight: 129 g

Conductor cross-section: 0,75 - 4,0 mm²

Temperatures

Max. operating temperature: +70 °C

Min. installation temperature: +5 °C

Min. operating temperature: -30 °C (without mechanical stress)

Colors

Color: Grey

Drawing markings

L: 250 mm

Ratings

Rated voltage: 250 ... 400 V

Degree of protection: IP20

Flammability rating: UL 94 V-2

Rated current: 20 A

ETIM class: EC002560

US specific

UL Rated current: 16 A

ETIM

ETIM

Width: 59 mm
Length: 60 mm
Height: 20 mm
Degree of protection (IP): IP20
Material housing: Polyamide
Nominal rated current: 20 A
Model: Plug
Halogen free: true
Connection type: Screw connection
Number of poles: 5
Nominal rated voltage: 400 V
Strain relief: true
Locking mechanism: Integrated in plug-in connector
Mechanical coding: true
Contact material: CuZn
Connection cross section (solid-core): 0.75 ... 4 mm²
Number of connections per pole: 1
Pollution degree: 2
Colour coding/contact insert: Grey
Max. continuous temperature resistance contact part: 70 °C
Max. continuous temperature resistance strain relief: 70 °C
Surface finish contacts: Silver-plated
Rated surge voltage: 4 kV
Connection cross section (fine-strand): 0.75 ... 4 mm²
Cable diameter: 6.5 ... 14.5 mm

Packaging

Default package

Unit: PCS
Size: 20

Pallet package

Unit: PCS
Size: 900