



PRODUCT SPECIFICATION

2017-06-16



6418677729850

NCL220TX07040G**Cable set**

Code	NCL220TX07040G
GTIN	6418677729850
Name	Cable set EnstoNet Grey, 4,0 m
Vendor	Ensto Finland Oy CEC

Technical specification**Dimensions**

Weight:	310 g
Conductor cross-section:	3 x 0,75 mm ²
Cable length:	4.0 m

Temperatures

Max. operating temperature:	+70 °C
Min. installation temperature:	+5 °C
Min. operating temperature:	-30 °C (without mechanical stress)

Electrical values

Nominal current A:	16 A
--------------------	------

Materials

Material:	Polyamide 66
-----------	--------------

Features

Cable type:	HF (S05Z1Z1-F)
Description male/female coupler:	

Basic

Code:

Ratings

Rated voltage:	≥ 250 V
Degree of protection:	IP20
Flammability rating:	UL 94 V-2

ETIM class: EC002587

ETIM

ETIM

Degree of protection (IP): IP20
Nominal rated current: 6 A
Number of poles: 2
Nominal rated voltage: 250 V
Total length: 4000 mm
Mechanical coding: 1

Packaging

Default package

Unit: PCS
Size: 20

Pallet package

Unit: PCS
Size: 1260