

T-blocks with wires and cables

Product code	GTIN	Description	Weight	Package
NAD5BS.WT025	6418677720642	White, 2.5 m	394.5 g	10
NAD5BS.WT025-L1	6418677709456	White, 2.5 m, with L1 connection	300 g	10
NAD5BS.WT025-L2	6418677709463	White, 2.5 m, with L2 connection	300 g	10
NAD5BS.WT025-L3	6418677709470	White, 2.5 m, with L3 connection	300 g	10
NAD5BS.BT025-L1	6418677709876	Black, 2.5 m, with L1 connection	307 g	10
NAD5BS.BT025-L2	6418677709883	Black, 2.5 m, with L2 connection	307 g	10
NAD5BS.BT025-L3	6418677709890	Black, 2.5 m, with L3 connection	307 g	10
NBD5BS.ST004	6418677723476	Blue, 0.4 m	94 g	30
NCD5BS.GT005	6418677723957	Grey, 0.5 m	104 g	50
NCD5BS.GT010	6418677715280	Grey, 1.0 m	177.7 g	50
NCD5BS.GT025	6418677715297	Grey, 2.5 m	394.5 g	10



Connecting boxes

Five-pole EnstoNet connecting box

The product can be used to connect the operating voltage and the control signal to the lighting fixture. The connecting wires are 250 mm in length.

Product code	GTIN	Description	Weight	Package
NGJDM532	6418677116254	White/blue (1, PE, N, A, B)	119 g	10



Six-pole EnstoNet connecting box

The product can be used to connect the operating voltage and the control signal to the lighting fixture. The NGJDM633M T connector is equipped with a sixth permanent live wire for emergency lights. The connecting wires are 250 mm in length.

Product code	GTIN	Description	Weight	Package
NGJDM633	6418677116209	White/blue (1, PE, N, A, B, C)	129.0 g	10
NGJDM633M	6418677709395	White/blue (1, PE, N, A, B, C), with A connection	129.0 g	10



Six-pole EnstoNet connecting box with a cable

The product can be used to connect the operating voltage and the control signal to the lighting fixture. The T connector is equipped with a 0.4 m cable outlet and comes with two cable options. The five-pole cable is used for power supply and the two 1.0 mm² wires are used for control signals. In the other version, the six-pole cable has an additional wire for emergency lights.

Product code	GTIN	Description	Weight	Package
NGJDM633S	6418677709401	White/blue 1, PE, N, A, B (black), C (red)	129.0 g	10
NGJDM633SM	6418677709418	White/blue (1, PE, N, A, B, C), with A connection	129.0 g	10



Six-pole EnstoNet connecting box with emergency light connectivity

The product can be used to connect the operating voltage, emergency light's voltage and the control signal to the lighting fixture. The connecting wires are 250 mm in length.

Product code	GTIN	Description	Weight	Package
NGJDM642	6418677116308	White/blue (1, PE, N, 2, A, B)	129.0 g	10

