



PRODUCT SPECIFICATION

2/28/2019



6418677688362

XLAD2

Distribution block

Code	XLAD2
GTIN	6418677688362
Name	Distribution block EnstoNet XL
	2-pole, 32 A, power
Description	T-distributors have one input and two outputs. The input is always located on the left side when looking at the connector mounted. The input is always connected to a female socket coupler and the outputs to male plug couplers. The T-distributor can be fixed to a wall or ceiling using max. Ø 5mm flat head screws or with cable ties.
Vendor	Ensto Finland Oy



Technical specification

Dimensions

Dimensions l x w x h:	108 x 146 x 36
-----------------------	----------------

Temperatures

Max. operating temperature:	70 °C
Min. installation temperature:	5 °C

Certificates

Standards:	EN 61535
------------	----------

Ratings

Rated voltage:	≥ 250 V
Degree of protection:	IP20
Flammability rating:	V-2
Rated current:	32 A
ETIM 7:	EC002567 Compact distributor for plug-in building installation

ETIM

ETIM

Number of inputs:	1
Length:	108 mm
Surface finish contacts:	Silver-plated
Mechanical coding:	true
Rated voltage:	250 V
Colour coding/contact insert:	Black
Material housing:	Other
Number of poles:	2
Width:	146 mm
Locking mechanism:	Integrated in plug-in connector
Mounting possibility:	Integrated
Number of outputs:	2
Halogen free:	true
Contact material:	CuZn
Degree of protection (IP):	IP20
Max. continuous temperature resistance strain relief:	70 °C
Pollution degree:	2
Type of distributor:	T-distributor
Rated current:	32 A
Height:	37 mm
Max. continuous temperature resistance contact part:	70 °C
Rated surge voltage:	4 kV

Packaging

Default package

Unit:	PCS
Size:	20
Length:	220 mm
Width:	220 mm
Height:	175 mm
Weight (net):	2.8 kg
Weight (brt):	1.157 kg
Volume:	8.47

Pallet package

Unit:	PCS
Size:	1500
Length:	1200 mm
Width:	800 mm
Height:	1025 mm

Weight (brt):	111.775 kg
Volume:	984