

Fibre Optic Dome Enclosure 01-04

V.3.1

Description

The dome enclosure is suitable for protecting fibre cable splices in branching applications. Its well-engineered, injection-moulded outer body makes it impenetrable to the elements. It can protect splices and ensure reliability with usage in ambient temperatures from -40°C to +65 °C. It can be placed in aerial, wall mounted or duct mounted locations.

Features / Benefits

- ▶ Holds up to 144 fibres
- ▶ Easy to re-enter
- ▶ Cable entry/exit, 1 oval, 5 round
- ▶ Integrated pressure valve
- ▶ Termination and splice kit included
- ▶ Integrated seal, airtight and waterproof
- ▶ Ideal for cable repair
- ▶ RoHS compliant
- ▶ Can be used in through, branch or mid-span splice locations
- ▶ Suitable for aerial, underground duct or direct burial applications

Technical Specification

SPECIFICATION		
Width:	Depth:	Weight:
223 mm	450 mm	2.26 kgs
Cable entry/exit, 1 oval 4 round.		



Ordering Information

DESCRIPTION	PART NO
48 Spilce dome enclosure	DOME01
72 Spilce dome enclosure	DOME02
96 Spilce dome enclosure	DOME03
144 Spilce dome enclosure	DOME04



+44 (0) 870 127 3330



+44 (0) 870 127 3331



sales@fibrefab.com



www.fibrefab.com