



SHB 20/1, rozbo n  krabice na povrch pro 1 p stroj, podle britsk ch norem; b l  (RAL 9010), rozte   roub  60 mm, otvory pro  rouby s mosaznou zd rkou, p edlisovan  otvory 1x pro hadici a 1x pro  lab

Shoda s normami: IEC/EN 60670, BS 4662

Objedn c  pokyn: lze objednat i v hloubce 28 mm (SSB)



materi�l		tepl. rozsah		
PVC		-5 �C/+60 �C		
typ	rozm�r [mm]	mb	vb	ref. �.
SHB 20/1	85x85x35	15	120	025 524

SHB 20/1, rozbo ovacia krabica na povrch, pre 1 p stroj, pod a anglick ch noriem; biela (RAL 9010), vzdialenos  otvorov pre upev ovacie skrutky 60 mm, otvory pre skrutky s mosadznou vlo kou, predlisovan  otvory 1x pre ochrann  r rku a 1x pre  lab

Zhoda s normami: IEC/EN 60670, BS 4662

Objedn vac  pokyn: Mo nos  objedna  aj v h bke 28 mm (SSB)

SHB 20/2, rozbo n  krabice na om tku pro 2 p stroje, podle britsk ch norem; b l  (RAL 9010), rozte   roub  60 mm, otvory pro  rouby s mosaznou zd rkou, p edlisovan  otvory 1x pro hadici a 1x pro  lab

Shoda s normami: IEC/EN 60670, BS 4662

Objedn c  pokyn: lze objednat s otvory pro hadice v proveden  12 x 20 mm (SHB 20/2) nebo 12 x 25 mm (SHB 25/2)



materi�l		tepl. rozsah		
PVC		-5 �C/+60 �C		
typ	rozm�r [mm]	mb	vb	ref. �.
SHB 20/2	147x87x32	10	80	034 347

SHB 20/2, rozbo ovacia krabica na povrch, pre 2 p stroje, pod a anglick ch noriem; biela (RAL 9010), vzdialenos  otvorov pre upev ovacie skrutky 60 mm, otvory pre skrutky s mosadznou vlo kou, predlisovan  otvory 1x pre ochrann  r rku a 1x pre  lab

Zhoda s normami: IEC/EN 60670, BS 4662

Objedn vac  pokyn: mo nos  objedna  s otvormi pre ochrann  r rky v preveden  12 x 20 mm (SHB 20/2), alebo 12 x 25 mm (SHB 25/2)

SBL, kryc  v  ko pro SHB; b l  (RAL 9010), zapad  do krabicov ho r fku, upevn n   rouby

Shoda s normami: IEC/EN 60670



materi�l		tepl. rozsah		
PVC		-5 �C/+60 �C		
typ	rozm�r [mm]	mb	vb	ref. �.
SBL 1	85x85	50	1200	009 335
SBL 3	147x87	50	1200	004 775

SBL, zapusten  kryt pre SHB; biely (RAL 9010), zapad  do obruby krabice, upevnenie skrutkami

Zhoda s normami: IEC/EN 60670