


# Data sheet

|                |  |
|----------------|--|
| ID             | <b>PKG OP BK</b>   |
| Description    | enclosure box, jetting water tight   |
| Properties     | for surface installation, suitable for damp locations, without pre-punched conduit entries |
| Colour         | grey, similar to RAL 7037  |
| Classification | AC 690 V, IP 40  |

Norms: ÖVE/ÖNORM EN 60670-22:2007



| Working temperature |                      | Degree of protection (IP) | UV-Level      |
|---------------------|----------------------|---------------------------|---------------|
| -25 to +60 °C       |                      | IP65                      | L2            |
| Art. no.            | Dimensions Ø/LxB x T | Small Package             | Large Package |
| 000 848             | 105 x 105 x 64 mm    | 5 pc                      | 50 pc         |
| 010 790             | 200 x 150 x 85 mm    | 2 pc                      | 12 pc         |
| 013 010             | 300 x 200 x 125 mm   | 1 pc                      | 4 pc          |

## Further technical details

| Details                      |                |
|------------------------------|----------------|
| Halogen free                 | False          |
| Tackable                     | False          |
| Number of inlets             | -              |
| Type of housing feed-through | None           |
| Equipped with                | None           |
| Cover model                  | Mounting cover |
| Explosion-tested version     | False          |
| Weatherproof                 | False          |
| Material                     | PVC-U          |

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.