


Data sheet

| | |
|------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Part No. | UPRM BK UV |
| Description | rigid conduit, with turbo grooves, with moulded-on coupler medium compression resistance, medium impact resistance |
| Colour | black, similar to RAL 9005 |
| Fire Behaviour | non flame propagating |
| Classification | 33411 |
| Compression resistance | > 750 N |



Standard: EN 61386-1, EN 61386-21



| | | | | |
|----------------------|------------------|-----------------------|------------------|-----------------------|
| Compressive strength | Impact strength | Operating temperature | Bending strength | UV stabilized |
| Medium (class 3) | Medium (class 3) | -25 to +60 °C | Rigid | true – up to 10 years |

| Art. No. | ED | ID | VPE small/medium/large |
|----------|-------|---------|------------------------|
| 108511 | 16 mm | 13 mm | 3 m / 111 m / 6216 m |
| 108512 | 20 mm | 16,8 mm | 3 m / 111 m / 3996 m |
| 108513 | 25 mm | 21,4 mm | 3 m / 57 m / 2622 m |
| 108514 | 32 mm | 27,8 mm | 3 m / 57 m / 1368 m |
| 108515 | 40 mm | 35,4 mm | 3 m / 21 m / 966 m |
| 108516 | 50 mm | 44,3 mm | 3 m / 21 m / 630 m |
| 108517 | 63 mm | 56 mm | 3 m / 21 m / 378 m |

Areas of Recommended Application

| Area | |
|-----------------------------------------------|------|
| Flush mounted (plaster) | True |
| Surface mounted | True |
| Suitable for concrete installation | True |
| Machine and systems installation | True |
| Suitable for subsurface installation (screed) | True |
| Outdoor installation | True |
| Suitable for installation on wood | True |
| Hollow wall | True |
| Underground installation | True |

Further technical details

| Details | |
|------------------------|-------|
| Halogen free | False |
| With sleeve | True |
| Fire retardant version | True |
| Material | PVC-U |

Cardboard packaging used is made from 100% waste paper and is fully recyclable, plastic packaging is fully recyclable.