


Data sheet

Part No.	HFXP Pro BK UV
Description	pliable insulating conduit with turbo grooves, halogenfree, corrugated medium compression resistance, medium impact resistance
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Classification	33432
Compression resistance	> 750 N

Standard: EN 61386-1, EN 61386-22, EN 60754, EN 50642, EN 61034



Compressive strength	Impact strength	Operating temperature	Bending strength	UV stabilized
Medium (class 3)	Medium (class 3)	-25 to +105 °C	Pliable	true – up to 10 years

Art. No.	ED	ID	Bending radius	PU	PU
099487	16 mm	9,9 mm	80 mm	50 m	2700 m
099380	20 mm	12,9 mm	100 mm	50 m	2700 m
099381	25 mm	17 mm	125 mm	50 m	1600 m
099382	32 mm	23,3 mm	160 mm	25 m	675 m
105483	40 mm	30 mm	200 mm	25 m	500 m
107532	50 mm	38,7 mm	250 mm	25 m	300 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	True
Machine and systems installation	False
Suitable for subsurface installation (screed)	True
Outdoor installation	True
Suitable for installation on wood	True
Hollow wall	True
Underground installation	True

Further technical details

Details	
Halogen free	True
With sleeve	False
Fire retardant version	True
Material	PP-Blend

Cardboard packaging used is made from 100% waste paper and is fully recyclable,
plastic packaging is fully recyclable.