


Data sheet

Part No.	UPRM GY
Description	rigid conduit, with turbo grooves, with moulded-on coupler medium compression resistance, medium impact resistance
Colour	grey, similar to RAL 7037
Fire Behaviour	non flame propagating
Classification	33411
Compression resistance	> 750 N



Standard: EN 61386-1, EN 61386-21



Compressive strength class	Impact strength	Operating temperature	Bending strength
Medium (class 3)	Medium (class 3)	-25 to +60 °C	Rigid

Art. No.	ED	ID	VPE small/medium/large
084201	16 mm	12,5 mm	3 m / 111 m / 6216 m
084202	20 mm	16,3 mm	3 m / 111 m / 3996 m
084203	25 mm	21,1 mm	3 m / 57 m / 2622 m
084204	32 mm	27,4 mm	3 m / 57 m / 1368 m
084205	40 mm	35,5 mm	3 m / 21 m / 966 m
084206	50 mm	45,1 mm	3 m / 21 m / 630 m
084207	63 mm	57,4 mm	3 m / 21 m / 378 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	True
Machine and systems installation	True
Suitable for subsurface installation (screed)	True
Outdoor installation	False
Suitable for installation on wood	True
Hollow wall	True
Underground installation	True

Further technical details

Details	
Halogen free	False
With sleeve	True
Fire retardant version	True
Material	PVC-U

Cardboard packaging used is made from 100% waste paper and is fully recyclable, plastic packaging is fully recyclable.