

5031.021.xxx, stabilizační objímka pro DE330S;
poniklovaná mosaz

Materiál

Ponikl. mosaz



-40 °C/+200 °C

5031.021.xxx, stabilizačná objímka pre DE330S;
poniklovaná mosadz

Shoda s normami:

EN 62444

EN 61386

typ	pro DE330S	id [mm]	mb [ks]	ref. č.
5031.027.007	08	7	50	081610
5031.027.009	11	9	50	081611
5031.027.011	14	11	50	081612
5031.027.013	16	13	50	077239
5031.027.016	18	16	50	081614
5031.027.021	23	21	25	081615
5031.027.029	31	29	25	081616
5031.027.036	40	36	20	081617
5031.027.048	51	48	10	081618



5031.028.xxx, stabilizační objímka pro DE331S;
poniklovaná mosaz

Materiál

Ponikl. mosaz



-40 °C/200 °C

5031.028.xxx, stabilizačná objímka pre DE331S;
poniklovaná mosadz

Shoda s normami:

EN 62444

EN 61386

typ	pro DE331S	id [mm]	mb [ks]	ref. č.
5031.028.007	07	7	50	081619
5031.028.009	10	9	50	081620
5031.028.011	13	11	50	080452
5031.028.013	15	13	50	081622
5031.028.016	17	16	50	065656
5031.028.021	22	21	25	076787
5031.028.029	29	29	25	080321
5031.028.036	38	36	20	081626



GM 8000, pojistná matice; poniklovaná mosaz

Materiál

Cu - měď



-40 °C/+200 °C

GM 8000, poistná matica; poniklovaná mosadz

Shoda s normami:

EN 62444

EN 61386

typ	závit	od [mm]	mb [ks]	ref. č.
GM 12 (8000.12)	M12 x 1,5	12	50	054178
GM 16 (8000.17)	M16 x 1,5	16	50	054179
GM 20 (8000.20)	M20 x 1,5	20	50	054180
GM 25 (8000.25)	M25 x 1,5	25	25	054277
GM 32 (8000.32)	M32 x 1,5	32	10	054268
GM 40 (8000.40)	M40 x 1,5	40	10	054260
GM 50 (8000.50)	M50 x 1,5	50	10	054079
GM 63 (8000.63)	M63 x 1,5	63	10	054019

