

GSR PB, ocelová trubka se závitem pro velmi vysoké mechanické zatížení; černě lakovaná (RAL 9005), standardní délka 3 m, oba konce trubky se závitem (jeden s našroubovanou spojkou)

Materiál

FE



55561



> 4000 N



ano



-45 °C/+250 °C



> 20,4 J

Shoda s normami:

EN 61386-1

EN 61386-21

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
GSR 16 PB	16	13,2	3	30	080210
GSR 20 PB	20	16,8	3	30	019913
GSR 25 PB	25	21,8	3	30	019914
GSR 32 PB	32	28,8	3	21	019915
GSR 40 PB	40	36,8	3	15	019916
GSR 50 PB	50	46,8	3	15	019917
GSR 63 PB	63	59,4	3	9	019918



GSR FV, ocelová trubka se závitem pro velmi vysoké mechanické zatížení; žárově pozinkovaná, standardní délka 3 m, oba konce trubky se závitem (jeden s našroubovanou spojkou)

Materiál

FE



55571



> 4000 N



ano



-45 °C/+400 °C



> 20,4 J

Shoda s normami:

EN 61386-1

EN 61386-21

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
GSR 16 FV	16	13,2	3	30	077416
GSR 20 FV	20	16,8	3	30	019920
GSR 25 FV	25	21,8	3	30	019921
GSR 32 FV	32	28,8	3	21	019922
GSR 40 FV	40	36,8	3	15	019923
GSR 50 FV	50	46,8	3	15	019924
GSR 63 FV	63	59,4	3	9	019925

