

Tuhé trubky bezhalogenové

Pevné rúrky bezhalogénové

HFIR 3M, tuhá trubka bez hrdla pro lehké mechanické zatížení; bílá (RAL 9010), délka 3 mMateriál
PP-směs

LSF0H



samožhášivý



22431



> 320 N



-25 °C/+105 °C



1J

Shoda s normami:
EN 61386-1
EN 61386-21, EN 60754
EN 50642, EN 61034



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č. WH bílá/biela
HFIR 16 xx 3m	16	12,9	102	6120	087178
HFIR 20 xx 3m	20	16,2	102	4080	087179
HFIR 25 xx 3m	25	21,0	60	2400	087180
HFIR 32 xx 3m	32	28,0	45	1350	087181
HFIR 40 xx 3m	40	35,0	30	1020	103797
HFIR 50 xx 3m	50	45,0	15	630	103798

HFBS 3M, tuhá pancéřová trubka bez hrdla pro vysoké mechanické zatížení; černá (RAL 9005), délka 3 mMateriál
PP-směs

LSF0H



samožhášivý



44241



> 1250 N



BK



-5 °C/+120 °C



6J

Shoda s normami:
EN 61386-1
EN 61386-21, EN 60754
EN 50642, EN 61034



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č. BK UV černá/čierna
HFBS 16 xx 3m	16	11,7	111	6216	099870
HFBS 20 xx 3m	20	15,2	111	3996	099871
HFBS 25 xx 3m	25	19,65	57	2622	099872
HFBS 32 xx 3m	32	26,0	57	1368	099873
HFBS 40 xx 3m	40	33,6	21	966	099874
HFBS 50 xx 3m	50	43,4	21	504	099875

HFIRM 3M, tuhá trubka s hrdlem pro lehké mechanické zatížení; světle šedá (RAL 7035), délka 3 mMateriál
PP-směs

LSF0H



samožhášivý



22431



> 320 N



-25 °C/+105 °C



1J

Shoda s normami:
EN 61386-1
EN 61386-21, EN 60754
EN 50642, EN 61034



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č. LG sv.šedá/sv.sivá
HFIRM 16 xx 3m	16	13,0	111	6216	087215
HFIRM 20 xx 3m	20	16,9	111	3996	087216
HFIRM 25 xx 3m	25	21,4	57	2280	087217
HFIRM 32 xx 3m	32	28,2	57	1368	087218
HFIRM 40 xx 3m	40	35,5	21	966	102952
HFIRM 50 xx 3m	50	45,1	21	630	102953