

HFPRM 3M, tuhá pancéřová trubka s hrdlem
pro střední mechanické zatížení; světle šedá (RAL 7035),
délka 3 m

Materiál
PP-směs



LSFOH



samozhášivý



33431



> 750 N



-25 °C/+105 °C



2J

Shoda s normami:

EN 61386-1
EN 61386-21, EN 60754
EN 50642, EN 61034

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
					LG sv.šedá/sv.sivá
HFPRM 16 xx 3m	16	11,1	111	6216	087223
HFPRM 20 xx 3m	20	15,0	111	3996	087224
HFPRM 25 xx 3m	25	20,0	57	2280	087225
HFPRM 32 xx 3m	32	26,7	57	1368	087226
HFPRM 40 xx 3m	40	34,0	21	966	098784
HFPRM 50 xx 3m	50	43,5	21	630	098785
HFPRM 63 xx 3m	63	55,5	21	378	098786



HFPRM 3M, tuhá pancéřová trubka s hrdlem
pro střední mechanické zatížení; černá (RAL 9005),
délka 3 m

Materiál
PP-směs



LSFOH



samozhášivý



33431



> 750 N



-25 °C/+105 °C



2J

Shoda s normami:

EN 61386-1
EN 61386-21, EN 60754
EN 50642, EN 61034

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
					BK černá/čierna
HFPRM 16 xx 3m	16	12,2	111	6216	087219
HFPRM 20 xx 3m	20	15,4	111	3996	087220
HFPRM 25 xx 3m	25	19,8	57	2280	087221
HFPRM 32 xx 3m	32	26,7	57	1368	087222
HFPRM 40 xx 3m	40	34,1	21	966	098781
HFPRM 50 xx 3m	50	43,5	21	630	098782
HFPRM 63 xx 3m	63	56,5	21	378	098783

