

HFX, ohebná trubka bezhalogenová pro lehké mechanické zatížení; bílá (RAL 9010), v balení po 100 m, 50 m nebo po 25 m

Materiál						
PP-směs	LSF0H	samozhášivý	23332	> 320 N	-15 °C/+105 °C	2J

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č. WH bílá/biela
HFX 16 xx 50m	16	10,5	50	2700	102309
HFX 20 xx 50m	20	13,7	50	2700	102310
HFX 25 xx 50m	25	17,9	50	1600	102311
HFX 32 xx 25m	32	24,3	25	675	102312
HFX 40 xx 25m	40	30,0	25	500	102313
HFX 50 xx 25m	50	38,5	25	300	102314



Shoda s normami:
EN 61386-1
EN 61386-22, EN 60754
EN 50642, EN 61034

HFX, ohebná trubka bezhalogenová pro lehké mechanické zatížení; světle šedá (RAL 7035), v balení po 100 m, 50 m nebo po 25 m

Materiál						
PP-směs	LSF0H	samozhášivý	23332	> 320 N	-15 °C/+105 °C	2J

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č. LG sv.šedá/sv.sivá
HFX 16 xx 50m	16	10,7	50	2700	102295
HFX 20 xx 50m	20	14,0	50	2700	102296
HFX 25 xx 50m	25	19,0	50	1600	102297
HFX 32 xx 25m	32	24,2	25	675	102298
HFX 40 xx 25m	40	30,6	25	500	102299
HFX 50 xx 25m	50	38,8	25	300	102300



Shoda s normami:
EN 61386-1
EN 61386-22, EN 60754
EN 50642, EN 61034

HFX, ohebná trubka bezhalogenová pro lehké mechanické zatížení; černá (RAL 9005), v balení po 100 m, 50 m nebo po 25 m

Materiál						
PP-směs	LSF0H	samozhášivý	23332	> 320 N	-15 °C/+105 °C	2J

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č. BK černá/čierna
HFX 16 xx 100m	16	10,0	100	4000	102302
HFX 20 xx 100m	20	14,0	100	4000	106057
HFX 25 xx 100m	25	18,0	100	2800	106058
HFX 32 xx 50m	32	24,0	50	1000	102305
HFX 40 xx 25m	40	30,0	25	500	102306
HFX 50 xx 25m	50	39,0	25	300	102307



Shoda s normami:
EN 61386-1
EN 61386-22, EN 60754
EN 50642, EN 61034