

HFXP, ohebná trubka pancéřová; HFT, s výbornou tvarovou pamětí (samoobnovující se), pro střední mechanické zatížení; černá (RAL 9005), v balení po 100 m a 25 m balení

Materiál
PP-směs



LSF0H



samozhášivý



33433



> 750 N



-25 °C/+105 °C



2J

Shoda s normami:

EN 61386-1
EN 61386-22, EN 60754
EN 50642, EN 61034



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č. BK černá/čierna
HFXP 16 xx 100m	16	10,0	100	4000	105750
HFXP 20 xx 100m	20	13,3	100	4000	104830
HFXP 25 xx 100m	25	17,5	100	2800	104831
HFXP 32 xx 25m	32	23,5	25	675	105751
HFXP 40 xx 25m	40	30,0	25	500	105752
HFXP 50 xx 25m	50	38,0	25	300	105753

HFXP Pro, ohebná trubka pancéřová pro střední mechanické zatížení; černá (RAL 9005), v balení po 50 m nebo po 25 m

Materiál
PP-směs



LSF0H



samozhášivý



33432



> 750 N



-25 °C/+105 °C



2J

Shoda s normami:

EN 61386-1
EN 61386-22, EN 60754
EN 50642, EN 61034



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č. BK černá/čierna
HFXP Pro 16 xx 50m	16	9,9	50	2700	087169
HFXP Pro 20 xx 50m	20	13,3	50	2700	104836
HFXP Pro 20 xx 100m	20	13,3	100	4000	104838
HFXP Pro 25 xx 50m	25	17,5	50	1600	104837
HFXP Pro 25 xx 100m	25	17,5	100	1400	104839
HFXP Pro 32 xx 25m	32	23,3	25	675	087172
HFXP Pro 40 xx 25m	40	30,0	25	500	087173
HFXP Pro 50 xx 25m	50	38,7	25	300	087174

HFXP Pro UV, ohebná trubka pancéřová; bezhalogenová, černá (RAL 9005), pro střední mechanickou zátěž, pro venkovní instalace nebo do betonu

Materiál
PP-směs



LSF0H



samozhášivý



33432



> 750 N



ano



-25 °C/+105 °C



2J

Shoda s normami:

EN 61386-1
EN 61386-22, EN 60754
EN 50642, EN 61034



typ	od [mm]	id [mm]	mb [ks]	vb [ks]	ref. č. BK UV černá/čierna
HFXP PRO 16 xx UV 50m	16	9,9	50	2700	099487
HFXP PRO 20 xx UV 50m	20	12,9	50	2700	099380
HFXP PRO 25 xx UV 50m	25	17,0	50	1600	099381
HFXP PRO 32 xx UV 25m	32	23,3	25	675	099382
HFXP PRO 40 xx UV 25m	40	30,0	25	500	105483
HFXP PRO 50 xx UV 25m	50	38,7	25	300	107532