

HFXP-HT, ohebná trubka pancéřová pro střední mechanické zatížení; černá (RAL 9005), v balení po 50 m nebo 25 m

Materiál
PC-směs



HFT



samozhášivý



33552



> 750 N



-45 °C/+150 °C



2J

Shoda s normami:
EN 61386-1
EN 61386-22
EN 60754, EN 50642

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
					BK černá/čierna
HFXP-HT 12 xx	12	9,0	50	4500	016574
HFXP-HT 16 xx	16	9,9	50	2700	011301
HFXP-HT 20 xx	20	13,9	50	2700	011302
HFXP-HT 25 xx	25	18,0	50	1600	011303
HFXP-HT 32 xx	32	23,5	25	675	011304
HFXP-HT 40 xx	40	30,0	25	500	013254
HFXP-HT 50 xx	50	38,5	25	300	013255
HFXP-HT 63 xx	63	54,0	25	175	019897



FXPY, ohebná trubka pro lehké mechanické zatížení; oranžová (RAL 2004), v balení po 100 m, 50 m nebo 25 m

Materiál
PP



bezhalogenový



22322



> 320 N



-15 °C/+90 °C



1J

Shoda s normami:
EN 61386-1
EN 61386-22, EN 60754
EN 50642, EN 61034

typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
					OR oranžová
FXPY 16 xx 100m	16	10,7	100	4000	065098
FXPY 20 xx 100m	20	13,0	100	4000	105486
FXPY 25 xx 50m	25	17,0	50	2000	105487
FXPY 32 xx 50m	32	24,3	50	1000	065101
FXPY 40 xx 25m	40	31,2	25	500	107363
FXPY 50 xx 25m	50	39,6	25	300	107364

