

Hliníkové tuhé trubky

SALR GY, hliníková trubka pro vysoké mechanické zatížení; Al Mg Si 0,5-F22, standardní délka 3 m

Materiál
AL



44561



> 1250 N



ano



-45 °C/+250 °C



> 6 J

Shoda s normami:
EN 61386-1
EN 61386-21



typ	od [mm]	id [mm]	mb [ks]	vb [ks]	ref. č.
SALR 16 GY	16	14,2	3	15	035458
SALR 20 GY	20	18,2	3	15	035250
SALR 25 GY	25	23,0	3	15	035251
SALR 32 GY	32	29,8	3	15	035252
SALR 40 GY	40	37,6	3	15	035253
SALR 50 GY	50	47,6	3	15	035254
SALR 63 GY	63	60,4	3	15	035255

Objednací pokyn: rozměry 16 mm - 25 mm lze objednat v ohybatelném provedení (Al Mg Si 0,5-F18)

GALR GY, hliníková rúrka pre vysoké mechanické zaťaženie; Al Mg Si 0,5-F22, štandardná dĺžka 3 m, oba konce rúrky so závitom (jeden s našroubovanou spojkou)

Materiál
AL



55561



> 4000 N



ano



-45 °C/+250 °C



> 20,4 J

Shoda s normami:
EN 61386-1
EN 61386-21



typ	od [mm]	id [mm]	mb [ks]	vb [ks]	ref. č.
GALR 16 GY	16	12,6	3	15	035177
GALR 20 GY	20	16,2	3	15	035178
GALR 25 GY	25	21,1	3	15	035179
GALR 32 GY	32	28,1	3	15	035180
GALR 40 GY	40	36,1	3	15	035181
GALR 50 GY	50	46,0	3	15	035182
GALR 63 GY	63	58,8	3	15	035183

ALUX, ohebná trubka; hliníková, standardní délka 1,5 m

Materiál
AL



22552



-45 °C/+150 °C

Shoda s normami:
EN IEC 61386-22



typ	od [mm]	id [mm]	mb [ks]	ref. č.
ALUX 25 1,5 m	25	21,5	10	108807
ALUX 32 1,5 m	32	28,2	10	108808
ALUX 40 1,5 m	40	36,5	10	108809

ALUX, ohybná rúrka; hliník, štandardná dĺžka 1,5 m