


SCLX, bezhalogenová příchytka (klip) s možností vzájemného bočního spojení; černá (RAL 9005) nebo šedá (RAL 7001), montáž šrouby Ø 4 mm, s aretovaným upevněním ke kabelové chráničce

Materiál
PA-směs



typ	od [mm]	mb [ks]	vb [ks]	ref. č.	
				GY šedá/sivá	BK černá/čierna
SCLX 16 xx	16	100	1600	043323	043322
SCLX 20 xx	20	100	1200	043325	043324
SCLX 25 xx	25	100	800	043327	043326
SCLX 32 xx	32	50	600	043329	043328
SCLX 40 xx	40	50	400	043331	043330
SCLX 50 xx	50	50	400	043333	043332

Shoda s normami:

EN 61386-1
EN 61386-23, EN 60754

SCLX-C, bezhalogenová spona; černá (RAL 9005) nebo šedá (RAL 7001), pro příchytky (klipy) SCLX

Materiál
PA-směs



typ	od [mm]	mb [ks]	vb [ks]	ref. č.	
				GY šedá/sivá	BK černá/čierna
SCLX-C 16 xx	16	100	4000	043335	043334
SCLX-C 20 xx	20	100	4000	043337	043336
SCLX-C 25 xx	25	100	4000	043339	043338
SCLX-C 32 xx	32	100	4000	043341	043340
SCLX-C 40 xx	40	100	3200	043343	043342
SCLX-C 50 xx	50	100	2400	043345	043344

Shoda s normami:

EN 61386-1
EN 61386-23, EN 60754

MFXE, flexibilní vlnitá kabelová chránička; z PE, pro lehké mechanické zatížení; černá (RAL 9005, UV-stabilní), balení po 100 m

Materiál
PE



typ	od [mm]	id [mm]	mb [m]	ref. č.
				BK UV černá/čierna
MFXE 1 xx	7,1	4,9	100	026328
MFXE 2 xx	10,0	7,2	100	026329
MFXE 3 xx	11,4	8,4	100	026330

Shoda s normami:

EN 61386-1
EN 61386-22

MFXP, flexibilní vlnitá kabelová chránička; z PP, pro lehké mechanické zatížení, bez kadmia; černá (RAL 9005, UV-stabilní), balení po 100 m

Materiál
PP



typ	od [mm]	id [mm]	mb [m]	ref. č.
				BK UV černá/čierna
MFXP 1 xx	7,1	4,9	100	035505
MFXP 2 xx	10,0	7,2	100	035506
MFXP 3 xx	11,4	8,4	100	035507

Shoda s normami:

EN 61386-1
EN 61386-22