


SFL, přírubová vývodka; bezhalogenová, černá (RAL 9005) nebo šedá (RAL 7001), bajonetový systém pro rychlou montáž, se 4 montážními otvory, vysoká pevnost v tahu

Materiál
PA-směs



Shoda s normami:


EN 61386-1
EN 61386-23, EN 60754



typ	od [mm]	mb [ks]	vb [ks]	ref. č.	
				GY šedá/sivá	BK černá/čierna
SFL 20 xx	20	50	400	020092	043005
SFL 25 xx	25	25	300	016520	043006
SFL 32 xx	32	20	160	016521	043007
SFL 40 xx	40	10	80	015072	043008
SFL 50 xx	50	6	48	015073	032663
SFL 63 xx	63	3	24	043011	043010

SFL S, přírubová vývodka; bezhalogenová, černá (RAL 9005) nebo šedá (RAL 7001), bajonetový systém pro rychlou montáž, se 4 montážními otvory, vysoká pevnost v tahu

Materiál
PA-směs



Shoda s normami:

EN 61386-1
EN 61386-23, EN 60754



typ	od [mm]	mb [ks]	vb [ks]	ref. č.	
				GY šedá/sivá	BK černá/čierna
SFL 20 S xx	20	50	400	043013	043012
SFL 25 S xx	25	25	300	019423	043014
SFL 32 S xx	32	20	160	019422	043015
SFL 40 S xx	40	10	80	015912	043016
SFL 50 S xx	50	6	48	015913	043017
SFL 63 S xx	63	3	24	043019	043018

SVG, přímá vývodka; Pg závit, bezhalogenová; IP54, černá (RAL 9005) nebo šedá (RAL 7001), bajonetový systém pro rychlou montáž, vysoká pevnost v tahu

Materiál
PA-směs



Shoda s normami:

EN 61386-1
EN 61386-23, EN 60754



typ	závit	od [mm]	mb [ks]	vb [ks]	ref. č.	
					GY šedá/sivá	BK černá/čierna
SVG 1207 xx	PG7	12	100	3200	043045	043044
SVG 1209 xx	PG9	12	100	3200	016893	043046
SVG 1609 xx	PG9	16	100	1600	017303	043080
SVG 1611 xx	PG11	16	100	1600	012683	042986
SVG 2011 xx	PG11	20	50	1200	017304	025091
SVG 2013 xx	PG13,5	20	50	1200	012684	061163
SVG 2516 xx	PG16	25	50	600	012685	043602
SVG 3221 xx	PG21	32	30	360	012686	043048
SVG 4029 xx	PG29	40	20	240	015070	043049
SVG 5036 xx	PG36	50	16	128	015071	043050
SVG 6348 xx	PG48	63	8	64	033506	043051