

Ocelové tuhé trubky

SSR PB, ocelová trubka pro vysoké mechanické zatížení; černě lakovaná (RAL 9005), standardní délka 3 m

Materiál
FE



44561



> 1250 N



ano



-45 °C/+250 °C



> 6 J

Shoda s normami:
EN 61386-1
EN 61386-21



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
SSR 16 PB	16	14,0	3	30	080212
SSR 20 PB	20	18,0	3	30	019899
SSR 25 PB	25	22,6	3	30	019900
SSR 32 PB	32	29,6	3	21	019901
SSR 40 PB	40	37,6	3	15	019902
SSR 50 PB	50	47,6	3	15	019903
SSR 63 PB	63	60,4	3	9	019904

SSR FV, ocelová trubka pro vysoké mechanické zatížení; žárově pozinkovaná, standardní délka 3 m

Materiál
FE



44571



> 1250 N



ano



-45 °C/+400 °C



> 6 J

Shoda s normami:
EN 61386-1
EN 61386-21



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
SSR 16 FV	16	14,0	3	30	080211
SSR 20 FV	20	18,0	3	30	019906
SSR 25 FV	25	22,6	3	30	019907
SSR 32 FV	32	29,6	3	21	019908
SSR 40 FV	40	37,6	3	15	019909
SSR 50 FV	50	47,6	3	15	019910
SSR 63 FV	63	60,4	3	9	019911

PSSR, ocelová trubka pro vysoké mechanické zatížení; pozinkovaná, standardní délka 4 m

Materiál
FE



44571



> 1250 N



-45 °C/+250 °C



> 6 J

Shoda s normami:
EN 61386-1
EN 61386-21



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
PSSR 16	16	14,0	40	800	081017
PSSR 20	20	18,0	40	800	081018