

UPRM 3M, tuhá pancéřová trubka s hrdlem
pro střední mechanické zatížení; s vnitřním podélným
drážkováním, světle šedá (RAL 7035), délka 3 m

Materiál
PVC-U


samožhášivý


33311


> 750 N


-15 °C/+60 °C


2J

Shoda s normami:
EN 61386-1
EN 61386-21



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
					LG sv.šedá/sv.sivá
UPRM 16 xx 3m	16	13,0	111	6216	084208
UPRM 20 xx 3m	20	16,8	111	3996	084209
UPRM 25 xx 3m	25	21,4	57	2280	084210
UPRM 32 xx 3m	32	27,8	57	1368	084211
UPRM 40 xx 3m	40	35,4	21	966	084212
UPRM 50 xx 3m	50	44,3	21	630	084213
UPRM 63 xx 3m	63	56,0	21	378	084214

UPRM 2M, tuhá pancéřová trubka s hrdlem
pro střední mechanické zatížení; s vnitřním podélným
drážkováním, světle šedá (RAL 7035), délka 2 m

Materiál
PVC-U


samožhášivý


33311


> 750 N


-15 °C/+60 °C


2J

Shoda s normami:
EN 61386-1
EN 61386-21



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.
					LG sv.šedá/sv.sivá
UPRM 16 xx 2m	16	13,0	74	4144	096366
UPRM 20 xx 2m	20	16,8	74	2516	108883
UPRM 25 xx 2m	25	21,4	38	1596	108884
UPRM 32 xx 2m	32	27,8	38	912	096369
UPRM 40 xx 2m	40	35,4	14	644	096370

UPRMS, tuhá trubka s hrdlem pro vysoké
mechanické zatížení; světle šedá UV (RAL 7035) nebo černá
UV (RAL 9005), délka 3 m

Materiál
PVC-U


samožhášivý


43411


> 1250 N


BK/LG


-25 °C/+60 °C


2J

Shoda s normami:
EN 61386-1
EN 61386-21



typ	od [mm]	id [mm]	mb [m]	vb [m]	ref. č.	
					BK UV černá/čierna	LG UV sv.šedá/sv.sivá
UPRMS 20 xx 3m	20	15,8	90	3780	100356	100351
UPRMS 25 xx 3m	25	20,6	90	2520	100357	100352
UPRMS 32 xx 3m	32	26,0	30	1500	100358	100353
UPRMS 40 xx 3m	40	34,0	30	990	100359	100354
UPRMS 50 xx 3m	50	43,0	30	450	100360	100355