

**VRM 3M**, tuhá trubka s hrdlom pro lehké mechanické zatížení; s vnitřním podélným drážkováním, světle šedá (RAL 7035), délka 3 m

|          |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                    |
|----------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Materiál |  |  |  |  |  |
| PVC-U    | samozhášivý                                                                       | 22211                                                                             | > 320 N                                                                           | -5 °C/+60 °C                                                                      | 1J                                                                                 |

Shoda s normami:  
EN 61386-1  
EN 61386-21

| typ          | od<br>[mm] | id<br>[mm] | mb<br>[m] | vb<br>[m] | ref. č.               |
|--------------|------------|------------|-----------|-----------|-----------------------|
|              |            |            |           |           | LG<br>sv.šedá/sv.sivá |
| VRM 16 xx 3m | 16         | 13,7       | 111       | 6216      | <b>084195</b>         |
| VRM 20 xx 3m | 20         | 17,4       | 111       | 3996      | <b>084196</b>         |
| VRM 25 xx 3m | 25         | 22,1       | 57        | 2622      | <b>084197</b>         |
| VRM 32 xx 3m | 32         | 28,6       | 57        | 1368      | <b>084198</b>         |
| VRM 40 xx 3m | 40         | 35,8       | 21        | 966       | <b>084199</b>         |
| VRM 50 xx 3m | 50         | 45,1       | 21        | 630       | <b>084200</b>         |



**VRM 2M**, tuhá trubka s hrdlom pro lehké mechanické zatížení; s vnitřním podélným drážkováním, světle šedá (RAL 7035), délka 2 m

|          |                                                                                    |                                                                                    |                                                                                    |                                                                                    |                                                                                     |
|----------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Materiál |  |  |  |  |  |
| PVC-U    | samozhášivý                                                                        | 22211                                                                              | > 320 N                                                                            | -5 °C/+60 °C                                                                       | 1J                                                                                  |

Shoda s normami:  
EN 61386-1  
EN 61386-21

| typ          | od<br>[mm] | id<br>[mm] | mb<br>[m] | vb<br>[m] | ref. č.               |
|--------------|------------|------------|-----------|-----------|-----------------------|
|              |            |            |           |           | LG<br>sv.šedá/sv.sivá |
| VRM 16 xx 2m | 16         | 13,7       | 74        | 4144      | <b>084415</b>         |
| VRM 20 xx 2m | 20         | 17,4       | 74        | 2516      | <b>108881</b>         |
| VRM 25 xx 2m | 25         | 22,1       | 38        | 1596      | <b>108882</b>         |
| VRM 32 xx 2m | 32         | 28,6       | 38        | 912       | <b>084419</b>         |
| VRM 40 xx 2m | 40         | 35,8       | 14        | 644       | <b>084420</b>         |



**UPRM 3M**, tuhá pancéřová trubka s hrdlom pro střední mechanické zatížení; s vnitřním podélným drážkováním, černá UV (RAL 9005) a šedá (RAL 7037), délka 3 m, verze BK UV i pro venkovní instalace

|          |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                      |                                                                                       |
|----------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Materiál |  |  |  |  |  |  |
| PVC-U    | samozhášivý                                                                         | 33411                                                                               | > 750 N                                                                             | BK                                                                                  | -25 °C/+60 °C                                                                        | 2J                                                                                    |

Shoda s normami:  
EN 61386-1  
EN 61386-21

| typ           | od<br>[mm] | id<br>[mm] | mb<br>[m] | vb<br>[m] | ref. č.               |                 |
|---------------|------------|------------|-----------|-----------|-----------------------|-----------------|
|               |            |            |           |           | BK UV<br>černá/čierna | GY<br>šedá/sivá |
| UPRM 16 xx 3m | 16         | 13,0       | 111       | 6216      | <b>108511</b>         | <b>084201</b>   |
| UPRM 20 xx 3m | 20         | 16,8       | 111       | 3996      | <b>108512</b>         | <b>084202</b>   |
| UPRM 25 xx 3m | 25         | 21,4       | 57        | 2622      | <b>108513</b>         | <b>084203</b>   |
| UPRM 32 xx 3m | 32         | 27,8       | 57        | 1368      | <b>108514</b>         | <b>084204</b>   |
| UPRM 40 xx 3m | 40         | 35,4       | 21        | 966       | <b>108515</b>         | <b>084205</b>   |
| UPRM 50 xx 3m | 50         | 44,3       | 21        | 630       | <b>108516</b>         | <b>084206</b>   |
| UPRM 63 xx 3m | 63         | 56,0       | 21        | 378       | <b>108517</b>         | <b>084207</b>   |

