

GU, spojka víka; bílá (RAL 9010)

Materiál					
ABS	bezhalogenový	samozhášivý	IP40	-5 °C/+60 °C	2J

typ	pro šířku žlabu [mm]	mb [ks]	vb [ks]	ref. č.
GU2012,5B	20	50	4800	105622
GU6040B	60	50	-	105628
GU10054B	100	20	1500	105634

Shoda s normami:
IEC 60754, EN 50085



TT, koncovka; bílá (RAL 9010)

Materiál					
ABS	bezhalogenový	samozhášivý	IP40	-5 °C/+60 °C	2J

typ	rozměr [mm]	mb [ks]	vb [ks]	ref. č.
TT2012,5B	9 x 23	50	4800	105623
TT6040B	41 x 63	25	750	105629
TT10054B	55 x 103	12	648	105635

Shoda s normami:
IEC 60754, EN 50085



S WH, dělicí přepážka; bílá (RAL 9010)

Materiál					
PC/ABS	bezhalogenový	samozhášivý	IP40	-5 °C/+60 °C	2J

typ	rozměr [mm]	mb [ks]	vb [ks]	ref. č.
S8040LH	200 x 40	50	-	105636
S10040LH	200 x 54	35	-	105637

Shoda s normami:
IEC 60754, EN 50085

