

KSM, dvojité spojka; černá (RAL 9005), pro pískotěsné spojení KSR nebo BR trubek

Materiál
PVC-U



N 450



-5 °C/+60 °C



Shoda s normami:

EN 61386-1, EN 61386-24

typ	od [mm]	ED [mm]	mb [ks]	ref. č.
KSM 50 BK	50	53,7	1	001930
KSM 63 BK	63	67,0	1	001931
KSM 75 BK	75	79,6	1	001932
KSM 90 BK	90	95,5	1	001933
KSM 110 BK	110	116,3	1	001934
KSM 125 BK	125	132,7	1	001935
KSM 140 BK	140	148,8	1	001936
KSM 160 BK	160	169,5	1	001937

KSB 30, násuvné koleno s rozšířeným hrdlem; černé (RAL 9005), pro pískotěsné spojení KSR nebo BR trubek, úhel 30°

Materiál
PVC-U



N 450



-5 °C/+60 °C



KSB 30, násuvné koleno s rozšířeným hrdlom; čierne (RAL 9005), pre pieskotesné spojenie KSR, alebo BR rúr, uhol 30°

Shoda s normami:

EN 61386-1, EN 61386-24

typ	od [mm]	ED [mm]	mb [ks]	ref. č.
KSB 50/30 BK	50	54,3	1	001820
KSB 63/30 BK	63	68,0	1	001821
KSB 75/30 BK	75	80,6	1	001822
KSB 90/30 BK	90	96,5	1	001823
KSB 110/30 BK	110	117,0	1	001824
KSB 125/30 BK	125	133,1	1	001825
KSB 160/30 BK	160	170,0	1	001827

KSB 45, násuvné koleno s rozšířeným hrdlem; černé (RAL 9005), pro pískotěsné spojení KSR nebo BR trubek, úhel 45°

Materiál
PVC-U



N 450



-5 °C/+60 °C



KSB 45, násuvné koleno s rozšířeným hrdlom; čierne (RAL 9005), pre pieskotesné spojenie KSR, alebo BR rúr, uhol 45°

Shoda s normami:

EN 61386-1, EN 61386-24

typ	od [mm]	ED [mm]	mb [ks]	ref. č.
KSB 50/45 BK	50	54,3	1	001836
KSB 63/45 BK	63	68,0	1	001837
KSB 75/45 BK	75	80,6	1	001838
KSB 90/45 BK	90	96,5	1	001839
KSB 110/45 BK	110	117,0	1	001840
KSB 125/45 BK	125	133,1	1	001841
KSB 140/45 BK	140	149,2	1	001842
KSB 160/45 BK	160	170,0	1	001843