

MIES, vnitřní úhel; bílý (RAL 9010)

Materiál
PVC-U -25 °C/+60 °C



typ	rozměr [mm]	mb [ks]	vb [ks]	ref. č.
MIES 50/50 WH	50 x 50	1	50	085632
MIES 50/100 WH	100 x 50	1	20	086043

Shoda s normami:
EN 50085, BS 4678 Part 4



MAES, vnější úhel; bílý (RAL 9010)

Materiál
PVC-U -25 °C/+60 °C



typ	rozměr [mm]	mb [ks]	vb [ks]	ref. č.
MAES 50/50 WH	50 x 50	1	50	085634
MAES 50/100 WH	100 x 50	1	20	086042

Shoda s normami:
EN 50085, BS 4678 Part 4



MK, spojka víka; bílá (RAL 9010)

Materiál
PVC-U samozhášivý -25 °C/+60 °C



typ	pro šířku žlabu [mm]	mb [ks]	vb [ks]	ref. č.
MK 50 WH	50	100	2400	019317
MK 75 WH	75	100	1600	019318
MK 100 WH	100	100	1200	019319
MK 150 WH	150	100	800	025055

Shoda s normami:
EN 50085, BS 4678/4



MHK, příchytka kabelů; bílá (RAL 9010)

Materiál
PVC-U samozhášivý -25 °C/+60 °C



typ	pro výšku žlabu [mm]	mb [ks]	vb [ks]	ref. č.
MHK 50 WH	50	50	800	019329
MHK 75 WH	75	50	800	019330
MHK 100 WH	100	50	400	019331

Shoda s normami:
EN 50085, BS 4678/4



MIES, vnútorný uhol; biely (RAL 9010)

MAES, vonkajší uhol; biely (RAL 9010)

MK, spojka veka; biela (RAL 9010)

MHK, príchytka káblov; biela (RAL 9010)