

SK, spojka; bílá (RAL 9010)

Materiál
PVC-U


 samozhášivý


 -5 °C/+60 °C


 1J

Shoda s normami:
 EN 50085, BS 4678/4



typ	rozměr [mm]	mb [ks]	vb [ks]	ref. č.
SK 16/16 WH	16 x 16	20	800	004951
SK 16/25 WH	16 x 25	20	800	004952
SK 16/40 WH	16 x 40	20	640	004953
SK 25/40 WH	25 x 40	20	640	004954
SK 40/40 WH	40 x 40	10	320	004955
SK 40/60 WH	40 x 60	5	200	025614

SFW, plochý úhel; bílý (RAL 9010)

Materiál
PVC-U


 samozhášivý


 -5 °C/+60 °C


 1J

Shoda s normami:
 EN 50085, BS 4678/4



typ	rozměr [mm]	mb [ks]	vb [ks]	ref. č.
SFW 16/16 WH	16 x 16	20	800	004956
SFW 16/25 WH	25 x 16	10	400	004957
SFW 16/40 WH	16 x 40	5	200	004958
SFW 25/40 WH	25 x 40	5	200	004959
SFW 40/40 WH	40 x 40	5	160	023003
SFW 40/60 WH	40 x 60	32	-	023612

SAE, vnější úhel; bílý (RAL 9010)

Materiál
PVC-U


 samozhášivý


 -5 °C/+60 °C


 1J

Shoda s normami:
 EN 50085, BS 4678/4



typ	rozměr [mm]	mb [ks]	vb [ks]	ref. č.
SAE 16/16 WH	16 x 16	20	800	004961
SAE 16/40 WH	16 x 40	10	400	004962
SAE 25/40 WH	25 x 40	10	400	004963
SAE 16/25 WH	16 x 25	10	400	004964
SAE 40/40 WH	40 x 40	10	160	023004
SAE 40/60 WH	40 x 60	24	-	023614