

Polishing Machine Cleaning Essentials



When polishing the ferrule of the connector it is essential that the process is kept clean, this ensures accurate and repeatable polishing. The recommended products to be used in the polishing process include low lint tissues and de-ionised water. Low Lint tissues are a versatile consumable for many applications. They are mainly used to clean bare fiber as part of the termination or splicing process. The low lint characteristic allows them to be used for a multitude of other purposes such as cleaning optical equipment and preparing work surfaces.

FEATURES/BENEFITS

- Super fast absorbency
- Can be used dry or with fluid
- Removes and absorbs dirt / grease /water / chemicals
- Tear resistant
- Strong non woven material
- Material: 44% wood pile tissue & 56% Terylene
- Size: 100mm x 100mm
- Thickness: 0.05mm
- Absorbency rate: 560%
- Absorbency speed: 5 seconds
- Class:10000

ORDERING INFORMATION

DESCRIPTION	PART NO.
AFL Hyperscale® Low Lint Cleaning Tissue - 100x100mm - Pack of 100	CLEANTISSUE/100
AFL Hyperscale® Low Lint Cleaning Tissue - 100x100mm - Pack of 400	CLEANTISSUE/400
De-ionised 1liter water bottle	WATERDEIONISED



SCAN QR FOR PRODUCT PAGE

FURTHER INFORMATION

- For additional information please contact your sales representative
- To view the product 360 visit the product page (Scan the QR code or visit the link below)
- Downloaded from <https://www.aflhyperscale.com/product/polishing-machine-cleaning-essentials>
- AFL Hyperscale reserves the right to make changes in this datasheet at any time without notice
- Information in this document is correct as of October 31, 2018

Europe

+44 (0) 1908 441 144
emeasales@aflhyperscale.com
© AFL Hyperscale 2019

Americas

+1 866 814 8615
usasales@aflhyperscale.com

Middle East & Africa

+971 4 404 9606
mesales@aflhyperscale.com

India

+91 80 46874687
indiasales@aflhyperscale.com

Asia Pacific

+86 755 2561 3694
apacsales@aflhyperscale.com